

Product Information

MOVING YOUR WORLD



SILKOLENE PRO KR2

Synthetic castor- and ester-based engine oil for 2-stroke kart racing.

Description

SILKOLENE PRO KR2 combines the outstanding wear and load carrying properties of castor oil with a clean combustion by modern synthetic technology, thus providing an exceptional engine performance, sustained power output and reliability. SILKOLENE PRO KR2 combats varnish deposits on and below the piston rings; it also reduces carbon deposits on the piston crown and in the exhaust ports thus enabling a more efficient ignition, essential when using the latest electronic power valve systems.

Application

SILKOLENE PRO KR2 is the ideal lubricant for all high-performance liquid- and air-cooled kart engines. Do not mix SILKOLENE PRO KR2 with other lubricants. For dilution ratios, please consult the manufacturer's recommendations. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages

- Specifically designed for kart engines.
- Ultimate engine protection under maximum racing conditions.
- Increased performance and reliability.
- Excellent load carrying capability ensures exceptional wear protection.
- Maintains engine cleanliness.
- Approved by CIK-FiA.

Specifications

- -

Approvals

- CIK-FIA (homologated)

FUCHS Recommendations

- -

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.944 g/ml
Kinematic Viscosity at 40°C	DIN 51562-1	95.9 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	11.1 mm ² /s
Viscosity Index	DIN ISO 2909	101
Closed Flash Point	ASTM D93	200 °C
Pour Point	DIN ISO 3016	-35 °C
Product Dyeing		Dark Orange/Red

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.